

STANDARD DEFINITION DIGITAL SET TOP BOX

SRT 5024X



- * DC 12/24V Power Supply
- * AC/DC Power Adaptor
- * DC 12/24 Vehicle Power Cable
- * USB 2.0 Host for playing video, MP3 and JPEG Files
- * Component Video Output
- * Auto & Manual Search
- * Closed Captions
- * Parental Lock



www.strong.com.au



Tuner

Guard Interval Modes	: 1/32, 1/16, 1/8, 1/4 Active Symbol Duration
FEC Mode Rates	: 1/2, 2/3, 3/4, 5/6, 7/8
Input Connector	: IEC 169-2, Female
Frequency Range	: 176-860MHz
Demodulator	: COFDM 2K/8K-Carrier
Channel Bandwidth	: 6/7/8MHz Switchable by Software (7MHz for Australia)

MPEG TS A/V Decoder

Video Resolution	: 720 x 576, 720 x 480	Audio Decoding	: MPEG/Musical Layer 1 & 2
Audio Mode	: Single / Dual Channel	Input Bit Rate	: Max. 90 Mbit/s
Transport Stream	: MPEG-2 ISO/IEC 13818-1		

A/V & Data Input/Output

Video	: RCA/Cinch Y, Pb, Pr (Component) : RCA/Cinch (CVBS) : 4 Pin Mini Din Connector - S-Video
Audio	: RCA/Cinch L/R with Volume & Mute Control (2 pairs) : Resolution: 20 bits DAC, Max 2 Vrms : S/PDIF for Dolby Digital and MPEG-2 Bit Stream Out
RS-232C	: Transfer Rate 115Kbps, 9 PIN D-Sub Type
USB 2.0	: Video File Type : *.MPG, *.DAT, *.VOB, *.AVI, *.Xvid & *.DivX (4.0 / 5.0) : Audio File Type : *.MP3 & *.WAV : Picture File Type : *.JPEG

System Resources

Flash Memory	: 1Mbyte
SDRAM	: 8Mbyte
Main CPU MPEG Chip	: SPHE1002

Power Supply

DC 124/24V, 1.2A Input - Supplied with DC 12V Power Pack and DC 14/24V Vehicle Power Cable	Power Consumption	: 13W Max. (Operating Mode)
--	-------------------	-----------------------------

Physical Specifications

Size (W x H x D)	: 250 x 38 x 175 (case) 185 (end of connectors) mm	E. & O. E.
Net Weight	: 1.9 Kg	
Operating Temperature	: 0°C - 50°C	

DISTRIBUTED BY:



STRONG AUSTRALIA PTY LTD 60 Wedgewood Road, Halam, Victoria 3803, Australia
Phone: +61 3 8795-7990 - Fax: +61 3 8795-7991 - Technical Support: 1 800 820 030

www.strong.com.au

sales@strong.com.au