

# HIGH DEFINITION 12/24V DIGITAL TELEVISION RECEIVER

## *SRT 5412*



- \* AC/DC Power Adaptor
- \* DC 12/24V Vehicle Power Cable
- \* USB 2.0 Host for firmware update
- \* Closed Captions
- \* MEPS Compliant
- \* Auto & Manual Channel Search
- \* Electronic Program Guide
- \* Parental Lock



[www.strong.com.au](http://www.strong.com.au)



## Tuner

Guard Interval Modes	: 1/32, 1/16, 1/8, 1/4 Active Symbol Duration	Signal Level	: -78.5 - -25dBm
FEC Mode Rates	: 1/2, 2/3, 3/4, 5/6, 7/8	Input Impedance	: 75
Input Connector	: IEC 169-2, Female	Wave Form	: OFDM
Frequency Range	: 174-862MHz	Carrier Mode	: 2K & 8K
Demodulator	: COFDM 2K/8K-Carrier		
Channel Bandwidth	: 6/7/8MHz Switchable by Software (7MHz for Australia)		

## MPEG TS A/V Decoder

Transport Stream	: MPEG-2 ISO/IEC 13818-1	Audio Decoding	: MPEG/Musical Layer & Dolby Digital
Profile Level	: MPEG-II MP@ML, MPEG-II MP@HL	Audio Mode	: Stereo / Joint Stereo / Mono
Video Resolution	: 720 x 576/p, 1280 x 720p & 1920 x 1080i	Sampling Rate	: 32KHz, 44.1KHz & 48KHz
	Selectable	Input Rate	: Max. 15 Mbit/s
Video Formats	: 4:3 Letterbox, 4:3 Pan & Scan, 16:9 Pillarbox & 16:9 Full Screen		

## A/V Input/Output

Video Output	: RCA/Cinch Y, Pb, Pr (Component)	S/PDIF	: Digital Audio Optical Output
	: RCA/Cinch (CVBS)	Audio	: RCA/Cinch L/R
	: 4 Pin Mini Din (S-Video)		
Digital A/V Output	: HDMI 1.2 (High Definition Multimedia Interface)		

## Data Input/Output

RS-232C	: Transfer Rate 115Kbps, 9 pin D-Sub Type	USB	: 2.0 Host
---------	-------------------------------------------	-----	------------

## System Resources

Main Processor	: CSM1100 32bit Super Scalar RISC CPU - ARM926EJ-S, 220MHz
Flash ROM	: 32Mbit
DDR DRAM	: 512Mbit

## Power Supply


DC 124/24V, 1.2A Input - Supplied with DC 12V Power Pack and DC 14/24V Vehicle Power Cable	Power Consumption: 13W Max. (Operating Mode)
--------------------------------------------------------------------------------------------	----------------------------------------------

## Physical Specifications

Size (W x H x D)	: 250 x 38 x 175 mm (185 end of connectors)
Weight	: 1.1 Kg
Operating Temperature	: 0°C - +50°C
Storage Temperature	: -40°C - +70°C

E. & O. E.

## DISTRIBUTED BY:



STRONG AUSTRALIA PTY LTD. - 60 Wedgewood Road, Hallam, Victoria 3803, Australia

Phone: +61 3 8795-7990 - Fax: +61 3 8795-7991 - Technical Support: 1 800 820 030

[www.strong.com.au](http://www.strong.com.au)

[sales@strong.com.au](mailto:sales@strong.com.au)