

HIGH DEFINITION DIGITAL VIDEO RECORDER

SRT5429A



Now with
500GB
Hard Drive

- Receives all Free to Air Digital Channels; HD & SD
- 500GB Built in Hard Drive, with additional storage via USB#.
- Record 1 program while watching another (from same network)
- Record and Playback, Time Shift, Pause and Rewind live TV
- USB 2.0 Host for Multimedia Playback; MP3, JPEG, and software updates. Supports MKV, TS, VOB, AVI, DivX and more.
- Electronic Program Guide with one touch record
- Closed Caption (record and playback)
- MPEG-4 compatible for record and playback 3D TV broadcasts.

USB External Hard Drive requires Fat32 format for recording



HD
HIGH DEFINITION

DOLBY
DIGITAL PLUS

HDMI
HIGH-DEFINITION MULTIMEDIA INTERFACE



DVR Digital
500 GB Video
Recorder



STRONG

www.strong.com.au



TUNER

Guard Interval Modes	: 1/32, 1/16, 1/8, 1/4 Active Symbol Duration	Signal Level	: -78.5 - -25dBm
FEC Mode Rates	: 1/2, 2/3, 3/4, 5/6, 7/8	Input Impedance	: 75 ohm
Input Connector	: IEC 169-2, Female	Wave Form	: OFDM
Frequency Range	: 174-230MHz, 474-868MHz	Carrier Mode	: 2K & 8K
Demodulator	: COFDM 2K/8K-Carrier		
Channel Bandwidth	: 7/8MHz Switchable by Software		

MPEG TS A/V Decoder

Transport Stream	: MPEG-2 ISO/IEC 13818-1	Audio Decoding	: MPEG/Musical Layer & Dolby Digital
Profile Level	: MPEG-II MP@ML, MPEG-II MP@HL	Audio Mode	: Stereo / Joint Stereo / Mono
	: MPEG-IV AVC/H.264 HP@L4.0	Sampling Rate	: 32KHz, 44.1KHz & 48KHz
Video Resolution	: 720 x 576i/p, 1280 x 720p & 1920 x 1080i	Input Rate	: Max. 15 Mbit/s
	Selectable		
Video Formats	: 4:3 Letterbox, 4:3 Pan & Scan, 16:9 Pillarbox & 16:9 Full Screen		

A/V Input/Output

Video Output	: CVBS, Audio Output L & R (RCA x 3)	Video Output	: Component Output, Y, Pb, Pr (RCA x 3)
Digital A/V Output	: HDMI 1.2 (High Definition Multimedia Interface)	Audio L/R	: RCA/Cinch (RCA x 2)
S/PDIF	: Digital Audio Output (RCA x 1)		

Data Input/Output

USB	: 2.0 Host
-----	------------

System Resources

Main Processor	: MSD7828L-LF (216MHz)	DDR DRAM	: 1024Mbit
Flash ROM	: 32Mbit		

Power Supply

Input Voltage	: AC 100-240V~, 50/60Hz	Power Consumption:	Max. 20W MEPS compliant
Type	: SMPS (Switching Mode Power Supply)		: Less than 1W on Stand-By Mode
		Protection	: Separate Internal Fuse

Physical Specifications

Size (W x D x H)	: 285 X 205 X 60mm (215mm to end of connectors)
Weight	: 1.38 kg
Operating Temperature	: 0°C ~ +50°C
Storage Temperature	: -40°C ~ +70°C

E. & O. E.

DISTRIBUTED BY:



STRONG AUSTRALIA PTY LTD. - 60 WEDGEWOOD ROAD, HALLAM, VICTORIA 3803, AUSTRALIA
 PH: +61 3 8795-7990 FAX: +61 3 8795-7991

TECHNICAL SUPPORT: 1 800 820 030

www.strong.com.au

sales@strong.com.au