

# 2 IN 1 COMBO UNIT

## HD DIGITAL SET TOP BOX WITH DVD PLAYER

*SRT6002*



Record Function  
via USB Hard Drive  
(Not Supplied)#



- High Definition Digital Set Top Box, MPEG-4 compliant  
\* Record and play back of 3D MPEG 4 Broadcast only.
- Record Function via USB External Hard Drive (Not Supplied)
- Video Resolution 1080i/720p/576p/i
- DVD/MP3/VCD/CD/CD-R/CD-RW/DVD+/-R/DVD+/-RW/MPEG4/ Kodak Picture CD
- DVD Play, pause, stop, fast forward, fast rewind, skip slow motion, zoom in & out
- HDMI, Component, Composite Digital Coaxial Audio outputs
- Multimedia support via USB; AVI, DivX, MPEG4 and more

# Can support both Fat32 and NTFS File types



**HD**  
HIGH DEFINITION

**DVD**  
VIDEO

**HDMI**  
HIGH-DEFINITION MULTIMEDIA INTERFACE



**DVR**  
ready  
Digital  
Video  
Recorder



**STRONG**

[www.strong.com.au](http://www.strong.com.au)



# SRT6002 SPECIFICATIONS



## DVD

Supported Disc Formats : DVD, DVD+R, DVD-RW, DVD-R, CD, CD-R, CD-RW  
 Supported File Formats : MPEG-1, MPEG-2, MPEG-3, DIVX4.xx - DIVX5.xx  
 Music & Picture Formats : MP3, WMA, JPEG, BMP

## TUNER

Guard Internal Modes	: 1/32, 1/16, 1/8, 1/4	Signal Level	: -77 ~ 10dBm
FEC Mode Rates	: 1/2, 2/3, 3/4, 5/6, 7/8	Input Impedance	: 75 ohm
Input Connector	: IEC 169-2, Female	Carrier Mode	: 2K, 4K & 8K
Frequency Range	: 174-230MHz, 474-860MHz		
Demodulator	: QPSK, 16QAM, 64QAM		
Channel Bandwidth	: 7Mhz		

## MPEG TS A/V Decoder

Transport Stream	: MPEG-2 ISO/IEC 13818-1	Audio Mode	: Stereo / Joint Stereo / Mono
Profile Level	: MPEG-II MP@ML, MPEG-II MP@HL : MPEG-IV AVC/H.264 HP@L4.0	Sampling Rate	: 32KHz, 44.1KHz & 48KHz
Video Resolution	: 720 x 576i/p, 1280 x 720p & 1920 x 1080i Selectable	Input Rate	: Max. 15 Mbit/s
Video Formats	: 4:3 Letterbox, 4:3 Pan & Scan, 16:9 Pillarbox & 16:9 Full Screen		

## A/V Input/Output

Video Output	: CVBS, Audio Output L & R	Video Output	: Component Output, Y, Pb, Pr
Digital A/V Output	: HDMI 1.2 (High Definition Multimedia Interface)	Audio L/R	: RCA/Cinch
S/PDIF	: Coaxial Digital Output		

## Data Input/Output

USB : USB 2.0

## Power Supply

Input Voltage	: AC 100-240V~, 50/60Hz	Power Consumption:	Max. 20W MEPS compliant : Less than 8W on Stand-By Mode
Type	: SMPS (Switching Mode Power Supply)		

## Physical Specifications

Size (W x D x H) : 360x38x255mm  
 Weight : 1.45Kg  
 Operating Temperature : 0°C ~ + 40°C  
 Storage Temperature : -40°C ~ +70°C

DISTRIBUTED BY:



STRONG AUSTRALIA PTY LTD. - 60 WEDGEWOOD ROAD, HALLAM, VICTORIA 3803, AUSTRALIA  
 PH: +61 3 8795-7990 FAX: +61 3 8795-7991

TECHNICAL SUPPORT: 1 800 820 030

[www.strong.com.au](http://www.strong.com.au)

[sales@strong.com.au](mailto:sales@strong.com.au)