

STRONG SRT 7000 Specifications



TUNER x 2

Guard Interval Modes	: 1/4, 1/8, 1/16, 1/32	Code Rate	: 1/2, 2/3, 3/4, 5/6, 7/8
Frequency Range	: 170 ~ 230 MHz (VHF) 470 ~ 862MHz(UHF)	Waveform	: COFDM
IF Bandwidth	: 7.8 MHz	Carrier Mode	: 2k and 8k mode
Input Impedance	: 75 Ω		

MPEG TRANSPORT STREAM & AV DECODING

Transport Stream	: MPEG-II ISO/OEC 13818-1	Audio Decoding	: Digital Dolby Plus
Profile Level	: MPEG-II MP@ML, MPEG-II@HL, MPEG-IV AVC.H.264 HP@L4.0	Audio Mode	: Stereo/Joint Stereo/Mono
Video Resolution	: 720 x 576, 1280 x 720P, 1920 x 1080i, 1080P	Sampling Rate	: 32KHz, 44.1KHz and 48KHz
Video Codecs	: MPEG, MPEG4, HD Divx3.11/4.11/5x/6x, Home Theatre		
Audio Codecs	: MPEG1/2/3 (MP3), Digital Dolby, Digital Dolby Plus, Window Media & Media Pro Audio		

AUDIO/VIDEO IN/OUTPUT

Video	: RCA/Cinch, Video Outputs (CVBS) : Component output (YPbPr) : HDMI (High Definition Multimedia Interface) : S-Video
Audio L/R	: RCA/Cinch, Volume and Mute control
S/PDIF	: Optical digital audio output
Audio/Video Input	: RCA/Cinch A/V Input x1 & Component Input (YCbCr) x 1 - via External devices, 576i input only

DATA PORT

USB	: USB 2.0 Host (USB Port x 1 front panel & 1 rear panel), A-type
Ethernet	: 1 x port RJ45, 10/100MB-Tx (for data transfer and internet access)
SD Card Slot	: Support SD card slot on front panel
RS-232 Serial	: 9pin D-sub male, Max 115K bps

SYSTEM RESOURCES

Processor	: 32bit processor (450MHz)	FLASH	: 8Mbyte
DDR SDRAM	: 128Mbyte x 2	EEPROM	: 256Kbit
Inbuilt Hard Disk Drive	: 500GB Hard Drive		

POWER SUPPLY

Input Voltage	: AC100~240V, 50~60Hz
Power Consumption	: Standby <1W, on mode Max 50W

GENERAL DATA

Dimensions	: 335 x 247 x 58.5mm (WxDxH)
Weight	: 3kg

STRONG AUSTRALIA PTY LTD - 60 WEDGEWOOD ROAD, HALLAM, VICTORIA, 3803 AUSTRALIA

PH: +61 3 8795-7990 FAX: +61 3 8795-7991

TECHNICAL SUPPORT: 1800 820 030 EMAIL: tech@strong.com.au

SALES EMAIL: sales@strong.com.au

www.strong.com.au